

Pipe Outlet To Flat Area With No Defined Channel

Notes

1. Apron lining may be riprap, grouted riprap, or concrete.
2. L_a is the length of the riprap apron as calculated using Plates 1.36d and 1.36e.
3. d = 1.5 times the maximum stone diameter but not less than 6 inches.



Pipe Outlet To Well-Defined Channel

PIPE OUTLET CONDITIONS

(OP) OUTLET PROTECTION

TOE REQUIREMENTS FOR RIPRAP BANK PROTECTION

(RR) RIP RAP



CONSTRUCTION OF A STRAW BALE BARRIER

(STB) STRAW BALE





CONSTRUCTION OF A SILT FENCE

(SF) SILT FENCE



Specific Application

This method of inlet protection is applicable where the inlet drains a relatively flat area (slopes no greater than 5 percent) where sheet or overland flows (not exceeding 0.5 cfs) are typical. The method shall not apply to inlets receiving concentrated flows, such as in street or highway medians.

STRAW BALE DROP INLET SEDIMENT FILTER

(IP) INLET PROTECTION



GRAVEL CONSTRUCTION ENTRANCE

(CE) CONSTRUCTION ENTRANCE



Class of bedding will be Class 'C' or 'D' or as specifically directed by City of Williamsburg.

Class 'C' to be used between all buildings; Class 'D' in all other locations.

TRENCH BEDDING

SANITARY SEWER SPECIFICATIONS

Sanitary sewer shall be 8" ductile iron pipe; sanitary laterals shall be 4" cast iron soil pipe. All sewer appurtenances shall be as shown on the plans or an approved equal as approved by the City of Williamsburg.

MATERIALS SPECIFICATIONS

Water service lines and appurtenances shall be of materials and construction in conformity with the standards and specifications of the City of Williamsburg.

STORM DRAINAGE SPECIFICATIONS

Storm sewer shall be reinforced concrete pipe Class II or an approved corrugated metal pipe as shown on the plans. An approved equal may be used if previously approved by the City of Williamsburg.



50' GRAVEL FILTER DETAIL

EROSION CONTROL NOTES

I THE CONTRACTOR SHALL COMPLY WITH THE APPLICABLE REGULATIONS OF THE VIRGINIA EROSION AND SEDIMENT CONTROL HANDBOOK, LATEST EDITION AND/OR CITY OF WILLIAMSBURG EROSION AND SEDIMENTATION CONTROL REQUIREMENTS

2 PRIOR TO ANY CLEARING, GRADING OR CONSTRUCTION, PROTECTIVE BARRIERS SHALL BE PLACED AROUND SPECIFIED TREES TO BE RETAINED ON THE SITE TO PREVENT THE DESTRUCTION OR DAMAGING OF TREES. THESE WILL BE LOCATED IN A CIRCULAR PATTERN WITH A RADIUS EQUAL TO THE LENGTH OF THE WIDEST OR LONGEST BRANCH. MATERIALS WILL NOT BE STOCKPILED WITHIN THIS DEFINED AREA AND VEHICLES AND OTHER EQUIPMENT ARE TO BE EXCLUDED TO AVOID SOIL COMPACTION. THE COST INCURRED TO THIS REQUIREMENT WILL BE THOSE SPECIFICALLY ALLOWED BY THESE STANDARDS AND SPECIFICATIONS

3 BOARD OR PIPES OF A MINIMUM [illegible] WILL NOT BE NAILED OR ATTACHED TO TREES DURING CONSTRUCTION OPERATIONS

4 [illegible] OPERATIONS [illegible] SHALL BE CUT AT AN AREA EQUAL TO [illegible] THE TREE CIRCUMFERENCE [illegible] FEET (EXAMPLE [illegible] ABOVE GROUND LINE IN INCHES) EXPRESSED IN FEET. (EXAMPLE [illegible] DIFFERENCE OF TEN INCHES SHOULD HAVE A 10' [illegible] IN ALL DIRECTIONS FROM THE TRUNK. THIS SHOULD APPLY TO DITCHING FOR ALL UTILITY SERVICES IF FEASIBLE.

5 [illegible] AND EXPOSED [illegible] AREAS [illegible] IMMEDIATELY AFTER [illegible] IF FAILURE OCCURS, [illegible] ARE TO BE [illegible] AND SEEDED AS SOON AS [illegible] ARE FREE [illegible] SHOULD BE [illegible]

6 ALL TREE [illegible] REMOVED [illegible] SHALL BE [illegible] OF PROPERLY AND OTHER DEBRIS. [illegible] SHALL BE [illegible] OF AT A "DUMP TRUCK".

7 [illegible] REPLACING TREES KILLED [illegible]

8 IF ORNAMENTAL TREES PROTECTED BY THE ABOVE STANDARDS [illegible] OF NORMAL CONSTRUCTION, THEY SHALL BE REPLACED BY [illegible] OF AT LEAST 3 INCHES CALIPER OF THE SAME SPECIES OR [illegible] QUALITY, AS SPECIFIED BY THE CITY ARBORIST

9 ALL EROSION CONTROL DEVICES SHALL BE INSTALLED WITH THE FIRST PHASE OF CONSTRUCTION AND SHALL REMAIN IN PLACE UNTIL FINAL GRADING AND PAVING

9 THE CONTRACTOR SHALL CONSTRUCT AND MAINTAIN SILT TRAP, SUFFICIENT TO PREVENT SOIL FROM BEING ERODED FROM THE SITE INTO ANY ADJACENT DRAINAGE SYSTEM DITCH OR WATER COURSES. ANY ERODED MATERIAL SHALL BE PROMPTLY REMOVED

10 CONSTRUCTION OPERATIONS SHALL BE MANAGED SO THAT AS MUCH OF THE SITE AS POSSIBLE IS LEFT UNDISTURBED DURING INSTALL AND VEGETATION

11 TEMPORARY SEEDING SHALL BE APPLIED PRIOR TO CONSTRUCTION IN AREAS INDICATED (SEE TEMPORARY SEEDING SCHEDULE AND SPECIFICATIONS)

12 ALL GRADED AREA MUST BE PERMANENTLY STABILIZED IMMEDIATELY FOLLOWING FINISH GRADING. (SEE PERMANENT SEEDING SCHEDULE AND SPECIFICATION.)

13 TEMPORARY STABILIZATION SHALL BE PROVIDED IN AREA [illegible] NOT BE INSTALLED OR DRAINAGE SYSTEMS [illegible] IMMEDIATELY AFTER INSTALLATION OF [illegible] SYSTEM IS COMPLETE

14 TEMPORARY AND PERMANENT ENTRANCES TO THE SITE SHALL HAVE A STABILIZED PAD. PADS AT ENTRANCES SHALL BE [illegible] TO EFFECTIVELY RELIEVE STREET TRACKING

MINIMUM RIP RAP STONE - 12" DIAMETER

THICKNESS - NOT LESS THAN 6"

LENGTH - NOT LESS THAN 50'

WIDTH - NOT LESS THAN FULL WIDTH OF ALL POINTS OF INGRESS OR EGRESS OR AS SPECIFIED ON THE PLANS

MAINTENANCE REQUIREMENTS - AS NECESSARY TO PREVENT TRACKING OR PLANTING MUD INTO PUBLIC RIGHTS-OF-WAY OR PARKING AREAS

THE CONTRACTOR SHALL CONSTRUCT AND MAINTAIN SILT TRAPS SUFFICIENT TO PREVENT SOIL BEING ERODED FROM THE SITE INTO ANY ADJACENT DRAINAGE SYSTEM, DITCH OR WATER COURSES

SEDIMENT SHALL BE REMOVED FROM EROSION AND SEDIMENT CONTROL STRUCTURES WHEN IT ACCUMULATES TO SUCH AN EXTENT AS TO IMPAIR THE NORMAL FUNCTION OF SUCH STRUCTURES

EROSION AND SEDIMENT CONTROL STRUCTURES SHALL BE INSPECTED AFTER EACH RAINFALL. STRUCTURES FOUND TO BE DAMAGED SHALL BE PROMPTLY REPAIRED

TEMPORARY SEEDING

I LIME & FERTILIZER

A LIME - 1 TON OF AGRICULTURAL GROUND LIMESTONE OR EQUIVALENT PER ACRE

B FERTILIZER - [illegible] OR EQUIVALENTS PER ACRE

WORK LIME AND FERTILIZER INTO THE SOIL IMMEDIATELY FOLLOWING SPREADING OPERATIONS. (USING A DISC OR OTHER SUITABLE TOOL). SURFACE SOIL SHALL BE WORKED TO A DEPTH OF 4 TO 6 INCHES

THE ABOVE NOTES APPLY TO AREAS WITHOUT THE BENEFIT OF A SOIL TEST. WHERE SOIL TEST IS AVAILABLE, SPECIFIC RECOMMENDATIONS FOR LIME AND FERTILIZER WILL BE PROVIDED BY THE VIRGINIA POLYTECHNIC INSTITUTE AND STATE UNIVERSITY EXTENSION SERVICE FOR EACH SITE

CONSTRUCTION REQUIREMENTS

1 All construction to be in accordance with the City of Williamsburg standards and specifications. The contractor is responsible to obtain copies of same

2 Water line construction to be in accordance with City of Williamsburg, Department of Public Utilities Standards and Specifications. The contractor is responsible to contact the director prior to construction for standards and any permits that should be required



II SEEDING (DATES AND RATES PER ACRE)

A AUGUST 1 TO DECEMBER 15

RYE - 3 BU OR
WHEAT - 2 BU OR
RYE GRASS - 2 1/2 TO 3 LBS

B FEBRUARY TO MAY 1

SPRING OATS - 3 BU OR
STRIPED OATS - 2 1/2 BU OATS PLUS KOREAN LESPEDEZA - 50 LB LESPEDEZA (HULLED AND INOCULATED)

C MAY 1 TO AUGUST 1

SUDANGRASS - 30 TO 40 LBS OR
MILLET - 30 TO 40 LBS OR
SUDAN - 30 TO 40 LBS

BROADCAST OR DRILL SEED UNIFORMLY AND COVER TO A DEPTH OF 1/4" TO APPROXIMATELY 2" DEPENDING ON THE SEED SELECTED, EXCEPT WHERE A GRASS DRILL IS USED, THE SEEDS SHALL BE COVERED AND THE SEEDBED PACKED BY THE USE OF A CULTIPACKER AGRICULTURAL CULTIPACKER. SPECIFICATIONS SHALL BE USED AT RIGHT ANGLES TO THE GENERAL SLOPE TO MINIMIZE EROSION

III MULCHING

A MULCH [illegible] AFTER COMPLETION OF SEEDING OPERATIONS UNTIL [illegible] OF [illegible] SMALL GRAIN STRAW AT THE RATE [illegible] PER ACRE

B [illegible] ALL AREAS BY [illegible]

[illegible]

II LIME AND FERTILIZER

A LIME - APPLY GROUND LIMESTONE [illegible] OF 2 TONS PER ACRE

B FERTILIZER - [illegible] OR EQUIVALENT

IF SOILS ARE CHIPPEY IT IS DESIRABLE TO HAVE LIME AND FERTILIZER RECOMMENDATIONS BASED ON TILL SOIL.

THE LIME AND FERTILIZER SHALL BE DISKED OR WORKED INTO THE SOIL TO A DEPTH OF [illegible]

III SEEDING

SEED ONE OF THE FOLLOWING MIXTURES AT THE RECOMMENDED RATE PER ACRE FOR AREAS WITHOUT TURF OR PERENNIALS

A. 40 - 70 LBS TALL FESCUE (KY 31)
1 LBS OF LADINO
6 LBS OF RED CLOVER

B 20 - 40 LBS. TALL FESCY (KY 31)
25 LBS. SERICEA LESPEDEZA FOR SPRING SEEDINGS

SEEDING DATES - FALL SEEDING DATES FROM AUGUST 1 - SEPTEMBER 15 ARE GENERALLY PREFERRED FOR THE AREA. SPRING SEEDING DATES WOULD BE FROM FEBRUARY TO MAY 1

IV SEED ONE OF THE FOLLOWING MIXTURES FOR AREAS WITH TURF REQUIREMENTS

TYPE OF GRASS	SEEDING RATE	SEEDING DATE
TALL FESCUE KENTUCKY 31	8 - 10 LBS PER 1,000 S.F.	FEB - MARCH SEPT - OCT
COMMON BERMUDA	SPRIG: SEEDING - 1 LBS/ 1,000 SQ FT (- HULL SEED) FALL SEEDING 9 LBS./1,000 SQ FT (UNHULLED SEED)	MAY - JUNE
TUFCOTE (BERMUDA)	SOD PLUG: ON 1 FT CENTER SPACES 1,000 SQ FT BROADCAST	MARCH JULY
[illegible]	SOD PLUG: ON 1 FT CENTER SPACES [illegible]	MARCH - JULY
ZOYSIA MEYER EMERALD	[illegible] CENTER [illegible]	[illegible] JULY

[illegible]

A MULCH - MULCH WITH ANY [illegible] ALL AREAS SEEDED, BEFORE OR AT THE RATE INDICATED. [illegible] OLD [illegible] SHALL BE [illegible] AT A RATE THAT PERMITS [illegible] SUN [illegible] GROWTH THROUGH THE [illegible]

B MULCHING IS REQUIRED ON ALL [illegible] EXCEPT 25' LOTS
1. SMALL [illegible] TO 2 TONS PER ACRE [illegible] SEEDED AND WITH 3 DAYS OF APPLICATION
2. WOOD FIBER MATERIALS - [illegible] PER ACRE

VI MAINTENANCE

A IRRIGATION - IF SOIL [illegible] IRRIGATED, [illegible] SEEDINGS AND PLANTINGS [illegible] GROWTH UNTIL THEY ARE FIRMLY [illegible]

B REPAIR - INSPECT ALL AREAS FOR PLANTING FAIL TO ANY MAKE NECESSARY REPAIR, REPLACEMENTS, AND RE-SEEDING AT THE PLANTING SEASON IF POSSIBLE

C LIME & FERTILIZER - SHALL BE APPLIED UNDER A MAINTENANCE PROGRAM THAT IS BASED ON SOIL FERTILITY TESTS TO MAINTAIN THE USE AND GENERAL APPEARANCE OF THE VEGETATIVE COVER DURING SUBSEQUENT GROWING SEASONS

SPECIAL SEEDING & MULCHING NOTE:

The above seeding and mulching notes should conform to Virginia Soil and Erosion Handbook (the pages are Section III, Seeding pp. 211-215; Mulching - Section III pp. 250) or as directed by the City of Williamsburg.

NO.	DESCRIPTION
1	[illegible]
2	[illegible]
3	[illegible]
4	[illegible]
5	[illegible]
6	[illegible]
7	[illegible]
8	[illegible]